



# CERTIFICATE



# "EU-TYPE EXAMINATION OF SAFETY COMPONENTS FOR LIFTS" №874K/TE/11.10.2017

"LIFT CERTIFICAT TU - SOFIA" - conformity assessment notified body with Permission № 108-OC/07.06.2016, issued by STATE AGENCY FOR METROLOGICAL AND TECHNICAL SURVEILLANCE (SAMTS) with European Identification № 2201

Verified on the basis of examinations and tests that the product described below is in accordance with the essential safety requirements of the Directive 2014/33/EU, introduced by the "Ordinance for the essential requirements and conformity assessment of lifts and the safety devices for lifts".

Applicant:

(name, address)

Aksoz Makina San Ve Tic Ltd Sti

Address: 1187. Sok No:8 Ostims, Ankara, Turkey

Manufacturer of the safety component:

(name, address)

Aksoz Makina San Ve Tic Ltd Sti

Name and type of the safety component:

**Progressive Safety Gear** 

Type: ALY01

Additional data for identification of the

safety component:

The additional data and technical characteristics are

according to "Annex 1" of this certificate

**Application form of Conformity assessment:** 

**Testing laboratory:** 

№ 874/21.09.2017

STL at "LIFT Certificat TU-Sofia"

Test report:

№ 874/07.10.2017

**Summary report of Conformity assessment:** 

№ 874/08.10.2017

**Applied Directives and Standards:** 

Directive 2014/33/EU - Annex IVA (Module B),

EN81-50:2014 - p.5.3

This certificate contains Annex 1 - "Technical Characteristic", which is an integral part of it. The certificate expires on the occurrence of changes in the conditions under which it was issue or after expiring the validity period. Please, check "valid until" date below.

to changes in the conditions under which Certificate 874K replaced certificate 874/10.10.2017, which exp it was issue.

Date of issue: 11 October 2017

Valid until: 11 October 2022

Certificate TU-Sofia":

Assoc. Prof. PhD Eng. Georgi Iliev /

## TECHNICAL CHARACTERISTICS

of safety component: Safety gear, Type: ALY01

#### 1. Application of the safety gear

The following progressive safety gear conforms to the safety requirements of the applied Directive and Standards. It must be use according to the scope of application, described in p.2 of this Annex 1.

### 2. Parameters of the safety gear

Safety Gear Type	Guide rail blade thickness (mm)	Rates speed (m/s)	Min. permissible masses (kg)	Max. permissible masses (kg)
ALY01	9 mm	1.60	600	1400
		1.20	600	1710
		1.00	600	1905
		0.80	600	2135
		0.63	600	2345
		0.50	600	2550
	16 mm	1.60	600	1700
		1.20	600	2150
		1.00	600	2405
		0.80	600	2720
		0.63	600	2970
		0.50	600	3200

Maximum tripping speed of the overspeed governor (m/s): 2.1

Type of guide rail: T70, T82, T89, T90, T114, T125, T127

Minimum width of the gripping area (mm): 12

Acting direction: bi-directional

Surface condition of the guide rails: Cold Drawn, Machined

State of guide rails lubrication: HLP 32, HLP 46

#### 3. Picture and drawing of the safety gear

